

SILICON COMPLEMENTARY QUAD TRANSISTOR



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR MPQ6700 is comprised of two 2N3904 (NPN) chips and two 2N3906 (PNP) chips to be used as dual complementary pairs for general purpose amplifier and switching applications.

MARKING: FULL PART NUMBER

	ATINGS: (T _A =25°C)	SYMBOL		UNITS		
Collector-Base Voltage		V _{CBO}	40	V		
Collector-Emitter Voltage		VCEO	40	V		
Emitter-Base Voltage		V _{EBO}	5.0	V		
Continuous Collector Current		IС	200	mA		
Power Dissipation (per transistor)		PD	500	mW		
Power Dissipation (total package)		PD	2.0	W		
Operating and Storage Junction Temperature		т _Ј , т _{stg}	-65 to +150	°C		
Thermal Resistance (total package)		Θ _{JA}	62.5	°C/W		
ELECTRICAL CHARACTERISTICS PER TRANSISTOR: (T _A =25°C)						
SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS		
I _{CBO}	V _{CB} =30V		50	nA		
IEBO	V _{EB} =4.0V		50	nA		
BVCBO	Ι _C =10μΑ	40		V		
BVCEO	I _C =10mA	40		V		
BVEBO	Ι _Ε =10μΑ	5.0		V		
V _{CE(SAT)}	I _C =10mA, I _B =1.0mA		0.25	V		
V _{BE(SAT)}	I _C =10mA, I _B =1.0mA		0.90	V		
h _{FE}	V _{CE} =1.0V, I _C =0.1mA	30				
h _{FE}	V _{CE} =1.0V, I _C =1.0mA	50				
h _{FE}	V _{CE} =1.0V, I _C =10mA	70				
fт	V _{CE} =20V, I _C =10mA, f=100MHz	200		MHz		
C _{ob}	V _{CB} =5.0V, I _E =0, f=100kHz		4.5	pF		
C _{ib}	V _{EB} =0.5V, I _C =0, f=100kHz (NPN)		12	pF		
C _{ib}	V_{EB} =0.5V, I _C =0, f=100kHz (PNP)		10	pF		




R2 (25-September 2018)





MPQ6700


SILICON COMPLEMENTARY QUAD TRANSISTOR


TO-116 CASE - MECHANICAL OUTLINE












PIN CONFIGURATION



LEAD CODE:

1) Collector Q1	Collector Q3	
2) Base Q1	9) Base Q3	
Emitter Q1	10) Emitter Q3	
4) No Connection	11) No Connection	
5) Emitter Q2	12) Emitter Q4	
6) Base Q2	13) Base Q4	
Collector Q2	14) Collector Q4	

MARKING: FULL PART NUMBER

R2 (25-September 2018)

www.centralsemi.com




T_A=25°C

1000

100

MPQ6700

SILICON COMPLEMENTARY QUAD TRANSISTOR




C_{ob}

10

V_R, Reverse Voltage (V)

100

NPN TYPICAL ELECTRICAL CHARACTERISTICS





T_A=25°C f=1.0MHz


0.1 | 0.1

R2 (25-September 2018)





MPQ6700

SILICON COMPLEMENTARY QUAD TRANSISTOR




PNP TYPICAL ELECTRICAL CHARACTERISTICS









www.centralsemi.com

R2 (25-September 2018)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- · Consolidated shipping options

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

ss your design challenges.

· Custom product packing

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits

Custom bar coding for shipments

Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>





Product End of Life Notification

PDN ID:	PDN01169
Notification Date:	3/26/21
Last Buy Date:	9/26/21
Last Shipment Date	3/26/22

Summary: The devices below manufactured in the TO-116 case are discontinued and now classified as End of Life (EOL); last time buy orders will be NCNR. Note: MPQ2222, MPQ222A, and MPQ3904 are NOT being discontinued and remain active devices.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

Central Part Number	Replacement
MPQ2369	N/A
MPQ2483	N/A
MPQ2484	N/A
MPQ2907	N/A
MPQ2907A	N/A
MPQ3467	N/A
MPQ3762	N/A
MPQ3798	N/A
MPQ3799	N/A
MPQ3906	N/A
MPQ6002	N/A
MPQ6100A	N/A
MPQ6502	N/A
MPQ6700	N/A
MPQ7043	N/A
MPQ7053	N/A
MPQ7093	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.