

LED Shoe Box Light

Catalog #:	
Project :	
Type :	Date:
Notes:	

TK-SAL2

DESCRIPTION

LED Shoebox light is perfect fixture for medium height parking lot poles and new construction applications in industrial, warehouse, manufacturing, commercial, office, residential, and hospitality facilities.

APPLICATIONS

Ideal for lighting general outdoor, wet location and commercial area lighting. Replaces Metal Halide for superior energy efficiency and slim aesthetics.



Specification Features

Controls / Dimming

High quality bi-level Motion sensor with increased energy savings (Optional) & Photocell

Warranty

5 Years Limited Warranty. See warranty documentation for more information

Certification

Wet Location Certified, safe and reliable. DLC Premium, UL certified.

Installation / Mounting

Luminaire is easy to Surface Mount install. Five Mounting Options: Direct, Slip Fitter, Square/Round Pole Bracket, Trunnion and U bracket.

Ordering Infor	mation	Example: TK-SAL2-150W-YXX-P			
Fixture Type	Wattage	CRI	сст	Options	Voltage
TK-SAL2 LED Shoe Box Light	60W 100W 120W 150W 200W 240W 300W	Y 7 - 70 8 - 80 9 - 90	XX 30 - 3000K 40 - 4000K 50 - 5000K 57 - 5700K	X Blank - Non-Dimmable D - Dimming P - Photocell M - Motion Sensor	Н Blank - 100 - 277V H - 200 - 480V



Techno USA LLC dba Techno LED Lights 2763 Meadow Church Road, Suite 140, Duluth, GA-30097 | Tel: 678-456-4810 | Fax: 678-456-4810 | Email: sales@technoledlights.com TechnoLED[™] is a registered trademark of Techno Electromech and Techno USA LLC. Specifications and Dimensions subject to change without notice. Atlanta | San Antonio | Los Angeles

LED Shoe Box Light

יים

Lighting Parameters	Dimensi	ons					
200	0-277VAC / 0-480VAC	207	f			226	Î
ССТ 400 570	00K,5000K, 00K	336 [13.2]		139		336 [13.2]	
CRI RA	>70					•••	
Lumen Efficiency 130	0lm/W						
Working temperature -40	F~104 F			and the second se	3] 541 [[21,3]		
Power Factor <u>></u> 0.	95 ^{'8} 12				142 [29.3]		
Frequency 50/	60 Hz	ĨĤĨ	øe	5 <u>8</u> 2.71			Ø68 [2.7]
Lifetime >50),000Hrs						
	be II/Type III/ be IV/ Type V	<u>11 P</u> 60-15		8 3.1]		200-300W	<u>140</u> [5:5]
Mounting Options							
Direct (DI)	Slip Fitter (SF)	Square/Re		Trunnior			racket
Additional Options	Slip Filler (SF)	Square/R	ouna	Turmor	1(1K)	UЫ	ackel
Currin Market							
Microwave Motion Sensor	Lightning arreste		ket base of hotocell	Sho	orting Cap		otocell to dawn)
Input Voltage: 100-277V	AC: SB-60W	/ SB-100W	SB-120W	SB-150W	SB-200W	SB-240W	SB-300W
Model Power	60W	100W	120W	150W	200W	240W	300W
Lumious Flux 130lm/V			15600LM	19500LM	26000LM	31200LM	39000LM
Replaces HID	180W	320W	400W	450W	600W	750W	1000W
LEDs Quantity	68	98	126	154	196	252	308
Input Voltage: 200-480V Model	AC: SB-HV-10	0.14/	SB-HV-150W	_	SB-HV-200W		SB-HV-300W
Power	3B-HV-10 100W		150W		200W		300W
Lumious Flux 130lm/		M	19500LM		26000LM		300W 39000LM
Replaces HID	320W		450W		600W		1000W
LEDs Quantity	98		154		196		308

Techno USA LLC dba Techno LED Lights 2763 Meadow Church Road, Suite 140, Duluth, GA-30097 | Tel: 678-456-4810 | Fax: 678-456-4810 | Email: sales@technoledlights.com TechnoLED™ is a registered trademark of Techno Electromech and Techno USA LLC. Specifications and Dimensions subject to change without notice. Atlanta | San Antonio | Los Angeles

Packing

ltem	Qty/CTN	Carton Size	Gross Weight	20GP	40GP	40HQ
60W	-	600 X 375 X150mm 23.62" X 14.76" X5.90"	6.9KG - SF 7.1KG - DI 6.8KG - TR	823pcs	1588pcs	2000pcs
100W			6.9KG - SF 7.1KG - DI 6.8KG - TR			
120W			6.82KG - SF 7.12KG - DI 6.7KG - TR			
150W	1PCS		6.82KG - SF 7.12KG - DI 6.7KG - TR			
200W		790 X 375 X150mm 31.10" X 14.76" X5.90"	9.75KG - SF 9.97KG - DI 9.53KG - TR	636pcs	1227pcs	1545pcs
240W	_		9.75KG - SF 9.97KG - DI 9.53KG - TR			
300W			9.35KG - TR 10.3KG - SF 10.6KG - DI 10.15KG - TR			

Techno USA LLC dba Techno LED Lights. 2763 Meadow Church Road, Suite 140, Duluth, GA-30097. Phone: 678-456-4810 | Fax: 678-456-4810 | Toll Free: 1 844-552-8272 sales@technoledlights.com | www.technoledlights.com



© 2020 Techno USA LLC. All rights reserved. Techno LED Lights reserves the right to make changes to specifications and/or discontinue any product at anytime without the notice . Information presented in this document is reliable and accurate, It does not represent any quotation or contract. No liability will be accepted by the contributor by the publisher for any consequences for its use. Reproduction in whole or part is prohibited without prior consent of the copyright owner. TK-SAL2_June-20