


Insulation Thickness 0.38mm  
Overall Diameter 2.1±0.1mm

Copper Conductor  
40/0.162mm  
Resistance  
(20° (Max). 22.4Ω/km)

Jacket Thickness 0.76mm  
Overall Diameter 6.8±0.2mm



Black

White

(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip		
Color	Component	Qty	Strip	ROJ	Color	SVT 18AWGX3C 105°C BLACK  Length: 1000±50 mm	Strip	ROJ	Color
40P Black 90±5° A	LT-202(10A 125V) (NEMA5-15P)	1	7±1	23±3	Black		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Black
Nickel-Plated	Plug Terminal	1	7±1	23±3	White		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	White
Nickel-Plated	UL Blades	2	7±1	26±3	Green		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Green
White	(202 Inner Body)	1							

**NOTE :**

1. PLUG : LT-202 AMERICAN TYPE
2. CONNECTOR : NA
3. CORD : SVT 18AWGX3C 105°C BLACK 1M
4. APPROVALS : UL C-UL
5. Supplier for flexible cord : I-SHENG
6. Hi-Pot Test:2000v/1min<1mA>

**Marking:**

I-SHENG:(UL) E88265 SVT SHIELED 105°C 3X18AWG(0.824mm<sup>2</sup>)  
300V VW-1 I-SHENG CSA LL81924 TYPE SVT SHIELED  
105°C 3X0.824mm<sup>2</sup>(18AWG) 300V VW-1

**Modification History**


		<b>DRAWER</b>	Aaron	<b>DATE</b>	20/11/05	<b>P/N</b>	800-1801-2-SVT0-BL-00100-2
		<b>APPROVE</b>		<b>REV.</b>	0	<b>Dr.No.</b>	1091109
			比例			<b>TOL.</b>	±5mm
	<b>DESCRIPTION</b>			<b>DATE</b>			<b>ALL DIMENSIONS IN mm</b>

**CnC Tech**  
Industrial Cable and Connector Technology