

Specification Sheet

Part Number: MMB.50M4



Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces.

The mounts have easy installation into predrilled holes allowing for faster use.

Masonry Cable Tie Mount, 1.24"L, 0.25" Hole Dia, 0.18" Max Cable Tie Width, PA66STHS, Black, 1000/pkg

Article Number 151-30001

Type MMB.5

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.

Short Description Masonry Cable Tie Mount, 1.24"L, 0.25" Hole Dia, 0.18" Max Cable Tie Width, PA66STHS, Black, 1000/pkg

Global Part Name MMB.5-PA66STHS-BK

Length L (Imperial)	1.24
Length L (Metric)	31.5
Fixation Method	with Fir Tree (Mounts)
Width W (Imperial)	0.375
Width W (Metric)	9.5
Cable Ties	T18 - T50
Height H (Imperial)	.37
Height H (Metric)	9.40
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	4.6
Panel Thickness Min (Imperial)	1.0
Panel Thickness Min (Metric)	25.4
Panel Thickness Max (Metric)	25.4
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.35 mm
Mounting Hole Diameter D Max (Metric)	6.35

Material	Polyamide 6.6, super tough, heat stabilized (PA66STHS)
Material Shortcut	PA66STHS
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988