HellermannTyton

Specification Sheet

Part Number: 184-11011

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1" x 1.5", Non-Adhesive, PVC, White, 30ft/Box

Article Number 184-11011

Type SLHD1X1.5

Color White (WH)

Quantity Per box

Product Description HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct

> features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

High Density Slotted Wall Wiring Duct, 1" x 1.5", Non-Adhesive, PVC, **Short Description**

White, 30ft/Box

	_	
Global	Dart	Nama
Giuuai	ган	INAILIE

SLHD1X1.5-PVC-WH

Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	1.57
Height H (Metric)	39.9
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-extinguishing

Reach Compliant (Article 33)

Operating Temperature

Halogen Free

No

+122°F (+50°C)

No

ROHS Compliant
Yes

Certification/Specification
CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 UL

UL Recognized (US)

Yes

Package Quantity (Imperial)
30.0

Package Quantity (Metric)
9.14

3925900000

© 2022 HellermannTyton. All Rights Reserved.

Customs Number

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions