



VMST30-30-M8-55-S/2PK

Ruland VMST30-30-M8-55-S/2PK, Rubber Bumper, 30mm OD, M8 Threaded Stud, 18mm Stud Length, 30mm Height, 55 Shore A Natural Rubber Jacket, Stainless Steel

2 pack



Description

Ruland VMST30-30-M8-55-S/2PK is a 2 pack of rubber bumpers, each with a threaded stud. An individual rubber bumper has a 30mm outside diameter, M8 threaded stud, 18mm stud length, and 30mm height. Rubber bumpers are used to dampen shock loads and reduce noise and wear on industrial equipment, machine doors, and floors or other surfaces which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. These rubber bumpers have a tapered (conical) shape for gentler accommodation of shock loads when compared to cylindrical types. A rubber bumper can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped holes on the component it will be mounted to. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. Rubber bumpers in this pack have 55 Shore A hardness for a balance of rigidity and shock absorption. Bodies are made from stainless steel allowing for increased corrosion resistance. These rubber bumpers are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	1.18 in (30 mm)	Height (H1)	1.18 in (30 mm)
Thread (TH)	M8 x 1.25	Plate Thickness (PT)	0.08 in (2 mm)
Stud Length (LS)	0.71 in (18 mm)	Spring Rate	200 lb/in (35 N/mm)
Shore Hardness	55A (+/- 5)	Max Deflection	0.30 in (7.6 mm)
Max Axial Load	58.45 lb (260 N)	Multipack Quantity	2
Geometry	Conical	Rubber Material	Natural Rubber
Metal Material	Stainless Steel	Metallic Body Finish	Bright
Manufacturer	JW Winco/ Otto Ganter	Country of Origin	Hungary
Weight (lbs)	0.140600	UPC	634529367384
Tariff Code	4016.99.6000	UNSPC	31162804
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		