

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting fixtures, electrical cables and components.



DIELECTRIC STRENGTH TESTER MODEL DV-25V-5

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 5 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting fixtures, electrical cables and components.



DIELECTRIC STRENGTH TESTER MODEL DV-25V-10

IINPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL DV-25VA-5**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
AMMETER	0-5 mA dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 5 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL DV-25VA-5V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: \pm 2% of full scale
AMMETER	0-5 mA dc Accuracy: \pm 2% of full scale
TRIP CURRENT	Adjustable 3-5 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



DIELECTRIC STRENGTH TESTER MODEL DV-25VA-5VE

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
AMMETER	0-5 mA dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 0.1-5 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL DV-25VA-10**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
AMMETER	0-10 mA dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL DV-25VA-10V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
AMMETER	0-10 mA dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 3-10 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL DV-25VA-10VE**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V dc @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V dc Accuracy: $\pm 2\%$ of full scale
AMMETER	0-10 mA dc Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 0.1-10 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)