



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE56015 thru NTE56018 TRIAC, 25 Amp

### **Description:**

The NTE56015 through NTE56018 series of TRIACs are high performance glass passivated PNPN devices in a TO220 type package designed for general purpose applications where moderate gate sensitivity is required.

### **Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Repetitive Peak Off-State Voltage ( $T_J = -40^\circ$ to $+125^\circ\text{C}$ , $R_{GK} = 1\text{k}\Omega$ ), $V_{DRM}$	
NTE56015 .....	200V
NTE56016 .....	400V
NTE56017 .....	600V
NTE56018 .....	800V
On-State Current (All Conduction Angles, $T_C = +85^\circ\text{C}$ ), $I_{T(RMS)}$	25A
Non-Repetitive On-State Current (Half Cycle), $I_{TSM}$	
60Hz .....	260A
50Hz .....	250A
Fusing Current ( $t = 10\text{ms}$ ), $I^2t$	312A <sup>2</sup> s
Peak Gate Current ( $t = 10\mu\text{s}$ Max), $I_{GM}$	4A
Peak Gate Dissipation ( $t = 10\mu\text{s}$ Max), $P_{GM}$	10W
Gate Dissipation ( $t = 20\text{ms}$ Max), $P_{G(AV)}$	1W
Operating Junction Temperature Range, $T_J$	$-40^\circ$ to $+125^\circ\text{C}$
Storage Temperature Range, $T_{stg}$	$-40^\circ$ to $+125^\circ\text{C}$
Thermal Resistance, Junction-to-Case, $R_{thJC}$	1.5K/W
Thermal Resistance, Junction-to-Ambient, $R_{thJA}$	60K/W
Lead Temperature (During Soldering, 1.6mm from case, 10sec max), $T_L$	$+250^\circ\text{C}$

### **Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off-State Leakage Current	$I_{DRM}$	$V_D = V_{DRM}$ , $R_{GK} = 1\text{k}\Omega$ , $T_J = +25^\circ\text{C}$	-	-	10	$\mu\text{A}$
		$V_D = V_{DRM}$ , $R_{GK} = 1\text{k}\Omega$ , $T_J = +125^\circ\text{C}$	-	-	3	mA
On-State Voltage	$V_T$	$I_T = 37.5\text{A}$ , $T_J = +25^\circ\text{C}$	-	-	1.4	V
On-State Threshold Voltage	$V_{T(TO)}$	$T_J = +125^\circ\text{C}$	-	-	0.85	V
On-State Slope Resistance	$r_T$	$T_J = +125^\circ\text{C}$	-	-	13	$\text{m}\Omega$

**Electrical Characteristics (Cont'd):** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate Trigger Current	$I_{GT}$	$V_D = 12\text{V}$ , Note 1	-	-	50	mA
Gate Trigger Voltage	$V_{GT}$	$V_D = 12\text{V}$ , All Quadrants	-	-	2.5	V
Holding Current	$I_H$	$R_{GK} = 1\text{k}\Omega$	-	-	50	mA
Critical Rate-of-Rise	$dv/dt$	$V_D = 0.67 \times V_{DRM}$ , $R_{GK} = 1\text{k}\Omega$ , $T_J = +125^\circ\text{C}$	500	-	-	V/ $\mu\text{s}$
Critical Rate-of-Rise, Off-State	$dv/dt_c$	$I_T = 25\text{A}$ , $di/dt = 11\text{A/ms}$ , $T_C = +85^\circ\text{C}$	5	-	-	V/ $\mu\text{s}$

Note 1. For either polarity of gate voltage with reference to electrode  $MT_1$ .

