

Technical Data Sheet Rev 05.220908

Chargeit! Mini 75W Dual Port USB-A & USB-C PD Charger w/ PPS & QC4.0 Support

Model Number: CG-PD60PPS





Type-CPD Type-AQC





Features

- USB-A with Quick Charge 3.0 technology that provide up to 18W
- USB-C with Power Delivery CYPD CCG3PA Chipset enables up to 60W
- Power Delivery (PD) Integration with Programmable Power Supply to intelligently detect your device and deliver the optimal voltage/current for specific devices
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall & Surface

Package Contents

- 2-Pin Terminal Block
- Charger

Specifications	
OVERVIEW	
Model No	CG-PD60PPS
Product Type	USB Chargers
Compliance	FCC RoHS
UPC	045079161368
Country of Origin	China
LED indicators	Power
Chipset	Cypress CCG3PA
PHYSICAL	
Ship Weight (lbs)	0.28 lbs
Ship Weight (kg)	0.13 kg
Item Weight	0.281 lbs
Length	3.48 inches
Width	1.99 inches
Height	1.03 inches
Material	Steel
Color	Black
Mountable	Surface Mount Wall Mount



Specifications Cont.		
CONNECTIONS		
USB Specification	Charging Only	
Maximum Data Rate	N/A	
Downstream Port Count	2	
Downstream Port Type	1x Type A (Charging) 1x Type C (Charging)	
Works as Standalone Charger	Y - Can be used without Host	
Can be Bus Powered	N - External Power Required	
Power		
Input Voltage	12 ~ 24V DC	
Min Input Voltage	9V DC	
Max Input Voltage (DO NOT EXCEED)	28V DC	
Power Connector	Phoenix 2-pin	
Idle Power Draw	5mA @ 12vDC	
Max Power Draw	78W	
Max Per Port Draw	60W	
Supported Charge Protocols	Apple Charge 2.4A BC 1.2 PD PPS QC 4.0 / 3.0 / 2.0	
ENVIRONMENTAL		
Operating Temperature	0C ~ 55C	
Storage Temperature	-20C ~ 75C	
Operating Humidity	5% to 95% RH	
OS SUPPORT		
Supported Operating Systems	OS independent - No software or drivers required	
WARRANTY		
Warranty Period	1 Year	
PRODUCT URL		
CG-PD60PPS Product Page	https://www.coolgear.com/product/usb-power-delivery-60w-high-power-industrial-adapter-charger- ccg3pa	