Key Tronic Page 1 of 2

Product Specs

Keyboards



1-800-262-6006

Classic-P1 & -P2

The Lifetime Classic-P1 and -P2 are high-quality, 104-key Windows Compatible keyboards that are perfect entry-level or basic replacement keyboard for any user.

The affordable Classic has all the durability and strength of the Lifetime line, built into a compact, space-saving design.

This keyboard features an extra large L-shaped Enter key and Windows application keys for easier Start and Task Manager operations. All keys are factory tested to withstand 20 million.

Affordable pricing and a Lifetime Guarantee make this 104-key keyboard a necessary addition to every user's PC.

This product meets the European Union RoHS initiatives.

Now shipping with Ergo Technology. Most keyboards use a standard 55 grams of force required to register every key, Ergo Technology has 5 different levels of force. From 35 grams to 80 grams - that correspond to the strength of the finger that touches the keys. The result is more comfort for your hands.

MODEL # CLASSIC-P1 (Beige/PS2 Cable)
MODEL # CLASSIC-P2 (Black/PS2 Cable))

KEYBOARD SKIN P/N # VIEW SEAL CTKEY



Sorry - Gray version no longer available

Click here for RoHS Certificate of Compliance

Click here for Section 508 Standards info

Click here for more info on Ergo Technology



Specifications

Keyboard Features:

Small footprint, "space-saving" enclosure Enhanced 104-key layout Three Windows keys Large L-shaped Enter key

Package Dimensions:

Height: 2.5 inches Length: 21 inches Depth: 11 inches Weight: 2.5 pounds

Keys withstand over 20 million keystrokes Ltd Lifetime warranty PS2 Straight cable Keyboard color - see above Manufactured in China **RoHS Compliant**

System Requirements:

Windows 3.1 or higher, or OS/2 PS/2 keyboard port or AT-style keyboard port

Agency Approvals:

- FCC Class B
- UL
- CSA

Environmental Data:

Operating temperature -- 0° to 40° C (non-operating) -- -20° to $+60^{\circ}$ C Operating humidity -- 5% to 90% non-cond. amb. temp. (non-operating) -- 0% to 95% non-cond. @ 40°C Operating altitude -0 to +10,000Shock(non-operating) -- 50 G Vibration(non-operating) -- 5 to 500 Hz, 4 G

Mechanical Data:

Tot. travel -- .150" +/- .020" Travel to peak -- .050" +/- .010" Peak force -- 2.0 oz +/- .6oz Fire point -- .120" nominal

Each Package Contains:

Keyboard User's guide

Product Dimensions:

Height -- 1.5 inches Length -- 17.9 inches Depth -- 6.75 inches

Electrical Data:

Max. input power -- +5 Vdc +/-.25 V @ 100mA Phantom key lockout Serial data output -- Synchronous 8-bit

