

GENERAL SPECIFICATIONS:

RATING: 2.5A / 250 V AC

CABLE TYPE / SIZE: H05VV-F, 3 X 0.75 mm ²

TEMPERATURE RATING: 70° C CABLE JACKET COLOR: BLACK

OVERALL LENGTH (L): $2050 \pm 50 \text{ mm}$ CABLE OUTER DIAMETER: $6.7 \pm 0.2 \text{ mm}$ END 'A' TERMINATION: IEC 320/C5 END 'B' TERMINATION: BRAZILIAN APPROVALS PLUG: INMETRO APPROVALS CONNECTOR: UL BR

NOTES:


1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

PACKING:

HANKING

L = 200 + 20 mm

200 <u>+</u> 20



RELEASEDBy N.Frost at 10:51 am, Nov 01, 2016



Contents of this document

prior notice

are subject to change without

INMETRO OCP 0004

PLUG:

Foot Note:

Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.

Limitation of Use: Globtek product are not authorized for use as mission critical components in life support,

mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

DASH NO.	PART NO		REV.	DESCRIPTION				NOTES
TABULATION BLOCK								
			TOLE DECIMAL .xx +/- 0xxx +/0	1 +/- 1* 05		obTek [®] , Inc. w.globtek.com	186 Veterans Dr. No Tel. 201-784-1000	
INIT.BY:	DO	ATE: 3/11/10	MILLIMETE .xx +/- 0.3 .xxx +/01	+/- 1°	DWG TITLE:	BRAZILIAN DETAC	CHABLE CORDSET	
DRAWN:	. INT	ATE: 3/11/10	FSCN No G, CC	SIZE A				REV. B
APRVD:	TIVI	ATE: 3/11/10	SCALE: NONE		PART NO: 204B4262M0712(R)		SHEET 1/1	