



hexagon thin nut ISO 4035-M2,5-04, pre-assembled
recommended screw length for applications with locking lever see table
tightening torque max. 20 Ncm

no.	part no.	PCB-thickness	contact length	a±0,1	screw length
1	09030009960	3,0±0,4	20,0±0,3	11,75	16,8±0,5
2	09030009961	4,0±0,4	20,0±0,3	10,7	16,8±0,5
3	09030009962	1,6±0,4	17,0±0,3	9,9	13,6±0,5
		4,8±0,4	20,0±0,3		16,8±0,5
4	09030009963	2,4±0,4	17,0±0,3	9,1	13,6±0,5
		5,6±0,4	20,0±0,3		16,8±0,5
5	09030009964	3,2±0,4	17,0±0,3	8,3	13,6±0,5
		6,4±0,4	20,0±0,3		16,8±0,5
6	09030009965	4,0±0,4	17,0±0,3	7,5	13,6±0,5
		7,2±0,4	20,0±0,3		16,8±0,5
7	09030009966	1,6±0,4	13,2±0,3	6,7	10,4±0,5
		4,8±0,4	17,0±0,3		13,6±0,5
8	09030009967	2,4±0,4	13,2±0,3	5,9	10,4±0,5
		5,6±0,4	17,0±0,3		13,6±0,5
9	09030009968	3,2±0,4	13,2±0,3	5,1	10,4±0,5
		6,4±0,4	17,0±0,3		13,6±0,5
10	09030009969	4,0±0,4	13,2±0,3	4,3	10,4±0,5

	All rights reserved Department EL PD	Created by STORCK	Inspected by TADJE	Standardisation HOFFMANN	Date 2020-04-15	State Final Release
		Title DIN Signal shroud type C and R screw-fixing				Doc-Key / ECM-Nr. 100077234/UGD/002/C 500000171160
HARTING Electronics GmbH D-32339 Espelkamp		Type TB	Number 0903000996X		Rev. C	Page 1/1