18 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 132117 SMA Jack Straight Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Γ		Connector A	A	Cable			Connector B		
E T C E C F F I I I I I I I I I I I I I I I I I	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132245 SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right Angle		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 18 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	132117 SMA JK RG174 RG SMA Jack Straight Solder Standard 50 Ohm Cable Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Straight 0°	316 LMR100 50O	
THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE Y CUSTOM CABLE INC. ACCEPT/ ESTABLISHES AND AGREEMENT			AND MUST NOT BE U FAL TO CUSTOM CAF CED OR TRANSCRIBF RITTEN CONSENT O NCE OF THIS DRAWI	DELE D 7 NG Part No:	SMA-RA-JK/SMA-ST-JK G174 18I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGT IS LESS THAN 12 INCHES		