SIEMENS

Data sheet

6AV6881-0AW12-3AA0

add-on bag for small tablet extension for transporting a tablet in a bag Further information, Quantity and content: see technical data



| Product type designation Transport pouch small Control elements Frame size/design Exceptional No Ergonomics Trackbalf rest No Ambient conditions Suited for outdoor use Yes; Washable Suited for outdoor use Yes; Washable Ambient temperature during operation -0 °C (Indoor/outdoor max. 60 °C (Indoor/outdoor max. 60 °C C Relative humidity Operation, max. 95 % Condensation permissible Yes; Applies only for case, not for contents Mechanics/material Yes; Applies only for case, not for contents Mechanics/material Yes; Applies only for case, not for contents Mechanics/material Yes; Approximate dimension Height 18 cm; Approximate dimension Depth 5 cm; Approximate dimension Depth 5 cm; Approximate dimension Depth 5 cm; Approximate dimension Depth 3 cm; Max. device depth Voerail depth < | General information | |
|---|---|--|
| Frame size/design No Ergonomics Frackball rest No Anblent conditions Suited for indoor use Yes; Washable Suited for indoor use Yes; Washable Ambient temperature during operation min. -30 °C; Indoor/outdoor max. 60 °C; Indoor/outdoor max. 60 °C Relative humidity Operation max. 95 % Condensation max. 95 % Condensation generation Mochanics/material Plastic Ves; Applies only for case, not for contents Mechanics/material Plastic Yes; 420 HD nylon Dimensions Width 18 cm; Approximate dimension Height 2 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max, device width Mounting cutout, height Overail depth 3 cm; Max, device height Overail depth 40 g Scop of supply Delivery quantity in pieces 1 Other Merchancise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH Overail depth Aton Ka c | Product type designation | Transport pouch small |
| • Exceptional No Ergonomics • Trackball rest No • Adjustable height No Ambient conditions Yes; Washable Suited for outdoor use Yes; Washable Suited for outdoor use Yes; Washable Ambient temperature during operation -30 °C; Indoor/outdoor • min. -30 °C; Indoor/outdoor • max. 60 °C; Indoor/outdoor Ambient temperature during storage/transportation -10 °C • max. 60 °C Relative humidity -00 °C • Operation, max. 95 % • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Machanics/material -10 °C • Plastic Yes; 420 HD nylon Dimensions | Control elements | |
| Ergonomics • Trackball rest No • Adjustable height No Ambient conditions Suited for indoor use Yes; Washable Suited for outdoor use Yes; Washable Ambient temperature during operation -30 °C; Indoor/outdoor • min. -30 °C; Indoor/outdoor • max. 60 °C; Indoor/outdoor • min. -10 °C • max. 60 °C • Relative humidity -0 potention, max. • Operation, max. 60 °C • Relative humidity • Operation, max. • Operation, max. 95 % • Condensation permissible Yes; 420 HD nylon Dimensions | Frame size/design | |
| • Trackball rest No • Adjustable height No Ambient conditions Suited for indoor use Suited for indoor use Yes; Washable Ambient temperature during operation • min. • min. -30 °C; Indoor/outdoor • max. 60 °C, Indoor/outdoor Ambient temperature during storage/transportation • nin. • max. 60 °C Relative humidity • Operation, max. • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material | Exceptional | No |
| • Adjustable height No Ambient conditions | Ergonomics | |
| Ambient conditions Suited for indoor use Yes; Washable Suited for outdoor use Yes; Washable Ambient temperature during operation • min. • max. 60 °C; Indoor/outdoor Ambient temperature during storage/transportation • min. • min. -10 °C • max. 60 °C Relative humidity • 0°C • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material Mechanics/material Material Yes; 420 HD nylon Otimensions Yes; 420 HD nylon Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Aproximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply Delivery quantity in pieces 1 Other Tatonka 6541.040 Manufa | Trackball rest | No |
| Suited for indoor use Yes; Washable Suited for outdoor use Yes; Washable Ambient temperature during operation | Adjustable height | No |
| Suited for outdoor use Yes; Washable Ambient temperature during operation -30 °C; Indoor/outdoor • min. -30 °C; Indoor/outdoor Ambient temperature during storage/transportation 60 °C; Indoor/outdoor Ambient temperature during storage/transportation -10 °C • max. 60 °C Relative humidity -0 °C • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material - Material - • Plastic Yes; 420 HD nylon Dimensions - Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 3 cm; Max. device depth Weight (without packaging) 35 g Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply Delivery quantity in pieces Delivery quantity in pieces 1 Other - Me | Ambient conditions | |
| Ambient temperature during operation -30 °C; Indoor/outdoor • max. 60 °C; Indoor/outdoor Ambient temperature during storage/transportation -10 °C • max. 60 °C Relative humidity -10 °C • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material | Suited for indoor use | Yes; Washable |
| • min. -30 °C; Indoor/outdoor • max. 60 °C; Indoor/outdoor Ambient temperature during storage/transportation -10 °C • max. 60 °C Relative humidity -10 °C • Operation, max. 60 °C Relative humidity -0 °C • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Material - • Plastic Yes; 420 HD nylon Pinensions - Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device depth Weight with opackaging) 35 g Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply - Delivery quantity in pieces 1 Other - Murchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Suited for outdoor use | Yes; Washable |
| • max. 60 °C; Indoor/outdoor Ambient temperature during storage/transportation -10 °C • min. -10 °C • max. 60 °C Relative humidity -00 peration, max. • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material | Ambient temperature during operation | |
| Ambient temperature during storage/transportation -10 °C • min. -10 °C • max. 60 °C Relative humidity 95 % • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material 1 Material • Plastic • Plastic Yes; 420 HD nylon Dimensions 18 cm; Approximate dimension Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device depth Veright (without packaging) 35 g Weight (without packaging) 40 g Scope of supply Delivery quantity in pieces Delivery quantity in pieces 1 Other Merchandise Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | • min. | -30 °C; Indoor/outdoor |
| • min10 °C• max.60 °CRelative humidity95 %• Operation, max.95 %• Condensation permissibleYes; Applies only for case, not for contentsMechanics/materialMaterialYes; 420 HD nylon• PlasticYes; 420 HD nylonDimensionsWidth18 cm; Approximate dimensionHeight12 cm; Approximate dimensionDepth5 cm; Approximate dimensionMounting cutout, width10 cm; Max. device widthMounting cutout, height14 cm; Max. device heightOverall depth3 cm; Max. device depthWeights40 gScope of supplyDelivery quantity in piecesDelivery quantity in pieces1OtherTATONKA GmbH | • max. | 60 °C; Indoor/outdoor |
| • max. 60 °C Relative humidity 95 % • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material 1 Material Yes; 420 HD nylon Dimensions 18 cm; Approximate dimension Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 34 cm; Max. device height Overall depth 3 cm; Max. device depth Weights 10 g Scope of supply 20 g Delivery quantity in pieces 1 Other 1 Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Ambient temperature during storage/transportation | |
| Relative humidity • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material | • min. | -10 °C |
| • Operation, max. 95 % • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material Material • Plastic Yes; 420 HD nylon Dimensions Width Height 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weights 40 g Scope of supply 0 g Delivery quantity in pieces 1 Other 1 Marchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | • max. | 60 °C |
| • Condensation permissible Yes; Applies only for case, not for contents Mechanics/material • Plastic • Plastic Yes; 420 HD nylon Dimensions • Vidth Height 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply 1 Delivery quantity in pieces 1 Other 1 Marchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Relative humidity | |
| Mechanics/material Material • Plastic Dimensions Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weights Weight (without packaging) Weight (with packaging) 35 g Weight (with packaging) 40 g Scope of supply Delivery quantity in pieces Delivery quantity in pieces 1 Other Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Operation, max. | 95 % |
| Material Yes; 420 HD nylon Dimensions 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weights 40 g Scope of supply 1 Delivery quantity in pieces 1 Other 1 Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Condensation permissible | Yes; Applies only for case, not for contents |
| • Plastic Yes; 420 HD nylon Dimensions 18 cm; Approximate dimension Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weights Weight (without packaging) Weight (with packaging) 35 g Scope of supply 1 Delivery quantity in pieces 1 Other 1 Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Mechanics/material | |
| Dimensions Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weights Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply Delivery quantity in pieces 1 Other Merchandise Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Material | |
| Width 18 cm; Approximate dimension Height 12 cm; Approximate dimension Depth 5 cm; Approximate dimension Mounting cutout, width 10 cm; Max. device width Mounting cutout, height 14 cm; Max. device height Overall depth 3 cm; Max. device depth Weights Weight (without packaging) Scope of supply 40 g Delivery quantity in pieces 1 Other 1 Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Plastic | Yes; 420 HD nylon |
| Height12 cm; Approximate dimensionDepth5 cm; Approximate dimensionMounting cutout, width10 cm; Max. device widthMounting cutout, height14 cm; Max. device heightOverall depth3 cm; Max. device depthWeightsWeight (without packaging)Weight (with packaging)35 gWeight (with packaging)40 gScope of supplyDelivery quantity in piecesMerchandiseYes; Tatonka 6541.040Manufacturer nameTATONKA GmbH | Dimensions | |
| Depth5 cm; Approximate dimensionMounting cutout, width10 cm; Max. device widthMounting cutout, height14 cm; Max. device heightOverall depth3 cm; Max. device depthWeightsWeight (without packaging)Weight (with packaging)35 gWeight (with packaging)40 gScope of supplyDelivery quantity in piecesDelivery quantity in pieces1MerchandiseYes; Tatonka 6541.040Manufacturer nameTATONKA GmbH | Width | 18 cm; Approximate dimension |
| Mounting cutout, width10 cm; Max. device widthMounting cutout, height14 cm; Max. device heightOverall depth3 cm; Max. device depthWeightsWeight (without packaging)Weight (with packaging)35 gWeight (with packaging)40 gScope of supplyDelivery quantity in pieces1OtherMerchandiseYes; Tatonka 6541.040Manufacturer nameTATONKA GmbH | Height | 12 cm; Approximate dimension |
| Mounting cutout, height14 cm; Max. device heightOverall depth3 cm; Max. device depthWeightsWeight (without packaging)35 gWeight (with packaging)40 gScope of supplyDelivery quantity in pieces1OtherMerchandiseYes; Tatonka 6541.040Manufacturer nameTATONKA GmbH | Depth | 5 cm; Approximate dimension |
| Overall depth3 cm; Max. device depthWeightsWeight (without packaging)35 gWeight (with packaging)40 gScope of supplyDelivery quantity in pieces1OtherMerchandiseYes; Tatonka 6541.040Manufacturer nameTATONKA GmbH | Mounting cutout, width | 10 cm; Max. device width |
| Weights Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply Delivery quantity in pieces Delivery quantity in pieces 1 Other Merchandise Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Mounting cutout, height | 14 cm; Max. device height |
| Weight (without packaging) 35 g Weight (with packaging) 40 g Scope of supply Delivery quantity in pieces Delivery quantity in pieces 1 Other Merchandise Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Overall depth | 3 cm; Max. device depth |
| Weight (with packaging) 40 g Scope of supply Image: Scope of supply Delivery quantity in pieces 1 Other Image: Scope of Supply Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Weights | |
| Scope of supply Delivery quantity in pieces 1 Other Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Weight (without packaging) | 35 g |
| Delivery quantity in pieces 1 Other Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Weight (with packaging) | 40 g |
| Other Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Scope of supply | |
| Merchandise Yes; Tatonka 6541.040 Manufacturer name TATONKA GmbH | Delivery quantity in pieces | 1 |
| Manufacturer name TATONKA GmbH | Other | |
| | Merchandise | Yes; Tatonka 6541.040 |
| Manufacturer's address Robert-Bosch-Straße 3, 86451 Dasing, Germany | Manufacturer name | TATONKA GmbH |
| | Manufacturer's address | Robert-Bosch-Straße 3, 86451 Dasing, Germany |

Subject to change without notice © Copyright Siemens

| Target devices | Suitable laptops and tablets, or similar |
|----------------------------------|---|
| Note: | Integrated cable inlets for power supply unit, hard disks etc simply flip open to get started |
| Usable in the following products | |
| Product 1 | 6AV7880-* |

last modified:

2/22/2022 🖸