

Number of contacts

6-64



Strain relief clamp/Locking lever

| Identification | No. of contacts | Part number | Drawing | Dimensions in mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|--|--|---|---|---|------|----|------|----|------|----|------|----|------|----|-------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|--|
| Strain relief clamp | 6 | 09 18 506 9002 | <table border="1"> <thead> <tr> <th>No. of contacts</th> <th>A</th> </tr> </thead> <tbody> <tr><td>6</td><td>12.2</td></tr> <tr><td>10</td><td>17.3</td></tr> <tr><td>14</td><td>22.4</td></tr> <tr><td>16</td><td>24.9</td></tr> <tr><td>20</td><td>30.0</td></tr> <tr><td>24</td><td>35.18</td></tr> <tr><td>26</td><td>37.6</td></tr> <tr><td>30</td><td>42.7</td></tr> <tr><td>34</td><td>47.8</td></tr> <tr><td>40</td><td>55.4</td></tr> <tr><td>50</td><td>68.1</td></tr> <tr><td>60</td><td>80.8</td></tr> <tr><td>64</td><td>85.9</td></tr> </tbody> </table> | No. of contacts | A | 6 | 12.2 | 10 | 17.3 | 14 | 22.4 | 16 | 24.9 | 20 | 30.0 | 24 | 35.18 | 26 | 37.6 | 30 | 42.7 | 34 | 47.8 | 40 | 55.4 | 50 | 68.1 | 60 | 80.8 | 64 | 85.9 | |
| | No. of contacts | A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 6 | 12.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10 | 17.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 14 | 22.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 16 | 24.9 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 20 | 30.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 24 | 35.18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 26 | 37.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 30 | 42.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 34 | 47.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 40 | 55.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 50 | 68.1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 60 | 80.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 64 | 85.9 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10 | 09 18 510 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 14 | 09 18 514 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 16 | 09 18 516 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 20 | 09 18 520 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 24 | 09 18 524 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 26 | 09 18 526 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30 | 09 18 530 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 34 | 09 18 534 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 40 | 09 18 540 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50 | 09 18 550 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 60 | 09 18 560 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 64 | 09 18 564 9002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| with bulk packaging | 6 | 09 18 506 9002 58U ³⁾ | 6 | 12.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10 | 09 18 510 9002 58U ³⁾ | 10 | 17.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 14 | 09 18 514 9002 58U ³⁾ | 14 | 22.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ³⁾ Packaging unit 5,000 pieces | 16 | 09 18 516 9002 58U ³⁾ | 16 | 24.9 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 20 | 09 18 520 9002 58U ³⁾ | 20 | 30.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ⁴⁾ Packaging unit 3,000 pieces | 26 | 09 18 526 9002 58U ³⁾ | 26 | 37.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 30 | 09 18 530 9002 58U ³⁾ | 30 | 42.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 34 | 09 18 534 9002 58U ⁴⁾ | 34 | 47.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 40 | 09 18 540 9002 58U ⁴⁾ | 40 | 55.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Locking lever for female connector Only in conjunction with low-profile male header and strain relief | | 09 18 000 9905 ¹⁾⁵⁾ 09 18 000 9905 58U ¹⁾⁶⁾ | | <p>When the security of latching is required and space is a premium, these locking levers can be fitted onto the strain relief of the HARTING female connector. This can then be used in conjunction with male low-profile headers (see pages 08.14 and 08.15).</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | ⁵⁾ Packaging unit 100 pieces ⁶⁾ Packaging unit 5,000 pieces | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Coding system with loss of contact Code pin | | 09 18 000 9901 ²⁾ | | <p>To avoid cross-plugging adjacent connectors a coding system is required. A code pin is inserted into the appropriate cavity in the female connector. The corresponding male contact is removed by a special removal tool.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Removal tool for male contacts | 09 99 000 0133 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

SEK

1) Order 2 per female connector
2) Part number comprises 6 code pins