

AD741 Series

FEATURES

Precision Input Characteristics

- Low V_{OS} : 0.5 mV max (L)
- Low V_{OS} Drift: 5 $\mu\text{V}/^\circ\text{C}$ max (L)
- Low I_b : 50 nA max (L)
- Low I_{OS} : 5 nA max (L)
- High CMRR: 90 dB min (K, L)

High Output Capability

$A_{OL} = 25,000$ min, 1 k Ω Load (J, S)


T_{min} to T_{max}

$V_o = \pm 10$ V min, 1 k Ω Load (J, S)

Chips and MIL-STD-883B Parts Available


FUNCTIONAL BLOCK DIAGRAMS

TO-99 (H) Package



NOTE: PIN 4 CONNECTED TO CASE

Mini-DIP (N) Package



HIGH OUTPUT CAPABILITY

Both the AD741J and AD741S offer the user the additional advantages of high guaranteed output current and gain at low values of load impedance. The AD741J guarantees a minimum gain of 25,000 swinging ± 10 V into a 1 k Ω load from 0 to $+70^\circ\text{C}$. The AD741S guarantees a minimum gain of 25,000 swinging ± 10 V into a 1 k Ω load from -55°C to $+125^\circ\text{C}$.

All devices feature full short circuit protection, high gain, high common-mode range, and internal compensation. The AD741J, K and L are specified for operation from 0 to $+70^\circ\text{C}$, and are available in both the TO-99 and mini-DIP packages. The AD741S is specified for operation from -55°C to $+125^\circ\text{C}$, and is available in the TO-99 package.

GENERAL DESCRIPTION

The Analog Devices AD741 Series are high performance monolithic operational amplifiers. All the devices feature full short circuit protection and internal compensation.

The Analog Devices AD741J, AD741K, AD741L, and AD741S are specially tested and selected versions of the standard AD741 operational amplifier. Improved processing and additional electrical testing guarantee the user precision performance at a very low cost. The AD741J, K and L substantially increase overall accuracy over the standard AD741C by providing maximum limits on offset voltage drift and significantly reducing the errors due to offset voltage, bias current, offset current, voltage gain, power supply rejection, and common-mode rejection. For example, the AD741L features maximum offset voltage drift of 5 $\mu\text{V}/^\circ\text{C}$, offset voltage of 0.5 mV max, offset current of 5 nA max, bias current of 50 nA max, and a CMRR of 90 dB min. The AD741S offers guaranteed performance over the extended temperature range of -55°C to $+125^\circ\text{C}$, with max offset voltage drift of 15 $\mu\text{V}/^\circ\text{C}$, max offset voltage of 4 mV, max offset current of 25 nA, and a minimum CMRR of 80 dB.


AD741 Series—SPECIFICATIONS (typical @ +25°C and ±15 V dc, unless otherwise specified)

Model	AD741C			AD741			AD741J			Units
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
OPEN-LOOP GAIN R _L = 1 kΩ, V _O = ±10 V R _L = 2 kΩ, V _O = ±10 V T _A = min to max R _L = 2 kΩ										V/V V/V V/V
	20,000	200,000		50,000	200,000		50,000	200,000		
OUTPUT CHARACTERISTICS Voltage @ R _L = 1 kΩ, T _A = min to max Voltage @ R _L = 2 kΩ, T _A = min to max Short Circuit Current										V V mA
	±10	±13 25		±10	±13 25		±10	±13 25		
FREQUENCY RESPONSE Unity Gain, Small Signal Full Power Response Slew Rate Transient Response (Unity Gain) Rise Time C _L ≤ 10 V p-p Overshoot										MHz kHz V/μs μs %
		1 10 0.5 0.3 5.0			1 10 0.5 0.3 5.0			1 10 0.5 0.3 5.0		
INPUT OFFSET VOLTAGE Initial, R _S ≤ 10 kΩ, Adjust to Zero T _A = min to max Average vs. Temperature (Untrimmed) vs. Supply, T _A = min to max										mV mV μV/°C μV/V
		1.0 1.0	6.0 7.5		1.0 1.0	5.0 6.0		1.0 3.0 4.0		
INPUT OFFSET CURRENT Initial T _A = min to max Average vs. Temperature										nA nA nA/°C
		20 40	200 300		20 85	200 500		5 50 100		
INPUT BIAS CURRENT Initial T _A = min to max Average vs. Temperature										nA nA nA/°C
		80 120	500 800		80 300	500 1,500		40 200 400		
INPUT IMPEDANCE DIFFERENTIAL	0.3	2.0		0.3	2.0		1.0			MΩ
INPUT VOLTAGE RANGE¹ Differential, max Safe Common-Mode, max Safe Common-Mode Rejection, R _S = ≤ 10 kΩ, T _A = min to max, V _{IN} = ±12 V										V V dB
		±12	±13		±12	±13		±15		
		70	90		70	90		80	90	
POWER SUPPLY Rated Performance Operating Power Supply Rejection Ratio Quiescent Current Power Consumption T _A = min T _A = max										V V μV/V mA mW mW mW
		±15			±15			±5	±15	±18
		30	150		30	150		2.2	3.3	
		1.7	2.8		1.7	2.8		50	85	
		50	85		50	85		60	100	
					45	75				
TEMPERATURE RANGE Operating Rated Performance Storage										°C °C
	0		+70	-55		+125	0		+70	
	-65		+150	-65		+150	-65		+150	

NOTES
¹For supply voltages less than ±15 V, the absolute maximum input voltage is equal to the supply voltage.

Specifications subject to change without notice.


All min and max specifications are guaranteed. Specifications shown in boldface are tested on all production units at final electrical test. Results from those tests are used to calculate outgoing quality levels.



Standard Nulling Offset Circuit

METALIZATION PHOTOGRAPH

All versions of the AD741 are available in chip form. Contact factory for latest dimensions. Dimensions shown in inches and (mm).



PAD NUMBERS CORRESPOND TO PIN NUMBERS FOR THE TO-99 8 PIN METAL PACKAGE.

Model	AD741K			AD741L			AD741S			Units
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
OPEN-LOOP GAIN										
$R_L = 1\text{ k}\Omega, V_O = \pm 10\text{ V}$							50,000	200,000		V/V
$R_L = 2\text{ k}\Omega, V_O = \pm 10\text{ V}$	50,000	200,000		50,000	200,000					V/V
$T_A = \text{min to max } R_L = 2\text{ k}\Omega$	25,000			25,000			25,000			V/V
OUTPUT CHARACTERISTICS										
Voltage @ $R_L = 1\text{ k}\Omega, T_A = \text{min to max}$	± 10	± 13		± 10	± 13		± 10	± 13		V
Voltage @ $R_L = 2\text{ k}\Omega, T_A = \text{min to max}$		25			25			25		mA
Short Circuit Current										
FREQUENCY RESPONSE										
Unity Gain, Small Signal		1			1			1		MHz
Full Power Response		10			10			10		kHz
Slew Rate		0.5			0.5			0.5		V/ μs
TRANSIENT RESPONSE (Unity Gain)										
Rise Time		0.3			0.3			0.3		μs
Overshoot		5.0			5.0			5.0		%
INPUT OFFSET VOLTAGE										
Initial, $R_S \leq 10\text{ k}\Omega$, Adjust to Zero		0.5	2.0		0.2	0.5		1.0	2	mV
$T_A = \text{min to max}$			3.0			1.0			4	mV
Average vs. Temperature (Untrimmed)		6.0	15.0		2.0	5.0		6.0	15.0	$\mu\text{V}/^\circ\text{C}$
vs. Supply, $T_A = \text{min to max}$		5	15.0		5	15.0		30	100	$\mu\text{V}/\text{V}$
INPUT OFFSET CURRENT										
Initial		2	10		2	5		2	10	nA
$T_A = \text{min to max}$			15			10			25	nA
Average vs. Temperature		0.02	0.02		0.02	0.1		0.1	0.25	nA/ $^\circ\text{C}$
INPUT BIAS CURRENT										
Initial		30	75		30	50		30	75	nA
$T_A = \text{min to max}$			120			100			250	nA
Average vs. Temperature		0.6	1.5		0.6	1.0		0.6	2.0	nA/ $^\circ\text{C}$
INPUT IMPEDANCE DIFFERENTIAL		2			2			2		M Ω
INPUT VOLTAGE RANGE¹										
Differential, max Safe		± 30			± 30			± 30		V
Common-Mode, max Safe		± 15			± 15			± 15		V
Common-Mode Rejection, $R_S \leq 10\text{ k}\Omega, T_A = \text{min to max},$ $V_{IN} = \pm 12\text{ V}$	90	100		90	100		90	100		dB
POWER SUPPLY										
Rated Performance		± 15			± 15			± 15		V
Operating	± 5		± 22	± 5		± 22	± 5		± 22	V
Power Supply Rejection Ratio		20			20			20		$\mu\text{V}/\text{V}$
Quiescent Current		1.7	2.8		1.7	2.8		2.0	2.8	mA
Power Consumption		50	85		50	85		50	85	mW
$T_A = \text{min}$								60	100	mW
$T_A = \text{max}$								75	115	mW
TEMPERATURE RANGE										
Operating Rated Performance	0		+70	0		+70	-55		+125	$^\circ\text{C}$
Storage	-65		+150	-65		+150	-65		+150	$^\circ\text{C}$

ABSOLUTE MAXIMUM RATINGS

Absolute Maximum Ratings	AD741, J, K, L, S	AD741C
Supply Voltage	$\pm 22\text{ V}$	$\pm 18\text{ V}$
Internal Power Dissipation	500 mW ¹	500 mW
Differential Input Voltage	$\pm 30\text{ V}$	$\pm 30\text{ V}$
Input Voltage	$\pm 15\text{ V}$	$\pm 15\text{ V}$
Storage Temperature Range	-65 $^\circ\text{C}$ to +150 $^\circ\text{C}$	-65 $^\circ\text{C}$ to +150 $^\circ\text{C}$
Lead Temperature (Soldering, 60 sec)	+300 $^\circ\text{C}$	+300 $^\circ\text{C}$
Output Short Circuit Duration	Indefinite ²	Indefinite

NOTES

¹Rating applies for case temperature to +125 $^\circ\text{C}$. Derate TO-99 linearity at 6.5 mW/ $^\circ\text{C}$ for ambient temperatures above +70 $^\circ\text{C}$.

²Rating applies for shorts to ground or either supply at case temperatures to +125 $^\circ\text{C}$ or ambient temperatures to +75 $^\circ\text{C}$.

ORDERING GUIDE

Model ¹	Temperature Range	Initial Off Set Voltage	Package Description	Package Option ²
AD741CN	0 to +70 $^\circ\text{C}$	6.0 mV	Mini-DIP	(N-8)
AD741CH	0 to +70 $^\circ\text{C}$	6.0 mV	TO-99	(H-08A)
AD741JN	0 to +70 $^\circ\text{C}$	3.0 mV	Mini-DIP	(N-8)
AD741JH	0 to +70 $^\circ\text{C}$	3.0 mV	TO-99	(H-08A)
AD741KN	0 to +70 $^\circ\text{C}$	2.0 mV	Mini-DIP	(N-8)
AD741KH	0 to +70 $^\circ\text{C}$	2.0 mV	TO-99	(H-08A)
AD741LN	0 to +70 $^\circ\text{C}$	0.5 mV	Mini-DIP	(N-8)
AD741LH	0 to +70 $^\circ\text{C}$	0.5 mV	TO-99	(H-08A)
AD741IH	-55 $^\circ\text{C}$ to +125 $^\circ\text{C}$	5.0 mV	TO-99	(H-08A)
AD741SH	-55 $^\circ\text{C}$ to +125 $^\circ\text{C}$	2.0 mV	TO-99	(H-08A)

NOTES

¹J, K and S grade chips also available.

²For outline information see Package Information section.

AD741 Series—Typical Performance Curves




Figure 1. Input Bias Current vs. Temperature




Figure 2. Input Offset Current vs. Temperature




Figure 3. Open-Loop Gain vs. Frequency




Figure 4. Open-Loop Phase Response vs. Frequency




Figure 5. Common-Mode Rejection vs. Frequency




Figure 6. Broad Band Noise vs. Source Resistance




Figure 7. Input Noise Voltage vs. Frequency




Figure 8. Input Noise Current vs. Frequency




Figure 9. Voltage Follower Large Signal Pulse Response




Figure 10. Output Voltage Swing vs. Supply Voltage




Figure 11. Output Voltage Swing vs. Load Resistance




Figure 12. Output Voltage Swing vs. Frequency