

Tone Generator & Probe Kit

Item: 400-011

- Fast, accurate wire identification
- Rugged industrial design
- Sends tone to identify wires
- Three selectable tone outputs
- Two-line polarity indication
- Continuity test
- Adjustable volume control
- Visual signal strength indication
- Powerful speaker for noisy environments
- Recessed telephone test set connectors



Tone Generator

Tone frequency	1kHz
Max. testing distance	1.5km
Max. working current	≤20mA
Tone mode	One / Two-note tone
Compatible connectors	De-energized AC wire, telephone/twisted pair wire, all voice
Function selection	TONE/OFF/CONT
Continuity test	1 LED (≤10Ω), Coaxial cable & solid/ stranded wire by alligator clips patch cord
Max. signal voltage	8Vp-p
LED indicator	Power indicator x1, Phone line polarity indicator x1, Phone line status indicator x1
Live telecommunication equipment test and router test	Y
Voltage protection	DC 48V
Low battery indication	7V(Flashing power indication)
Battery type	DC9.0V × 1pc, <i>not included</i>
Dimension(L x W x H)	2.6 x 2.3 x 1.3 in.
Weight	0.14 lbs

Amplifier Probe

Frequency	1kHz
Max. working current	≤70mA
Function selection	4 Position mode switch (LED, NCV, OFF, SCAN)
Earphone socket	1
Signal status indication	LED & Buzzer
NCV indication	LED (AC 90~1000V)
LED illumination	Y
Power indication	LED x 1
Battery type	DC9.0V × 1pc, <i>not included</i>
Dimension(L x W x H)	9.0 x 2.2 x 1.0 in.
Weight	0.18 lbs
Accessory	Storage bag



Order Today! SalesSupport@EclipseTools.com

Eclipse Enterprises, Inc. ● Tel: 804.561.2610 ● Fax: 804.561.2642

13302 Chula Road, Amelia Court House, VA 23002 ● EclipseTools.com