

## Han 3A HSI M20



Image is for illustration purposes only. Please refer to product description.

Part number	19 20 003 0102
Specification	Han 3A HSI M20
HARTING eCatalogue	<a href="https://b2b.harting.com/19200030102">https://b2b.harting.com/19200030102</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han A <sup>®</sup>
Type of hood/housing	Screw mounted housing

### Version

Size	3 A
Cable entry	1x M20
Locking type	Single locking lever
Field of application	Standard Hoods/housings for industrial applications

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67 with seal screw 09 20 000 9918
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0



**Pushing Performance**  
Since 1945

## Specifications and approvals

Approvals	DNV GL
CE	Yes

## Commercial data

Packaging size	10
Net weight	16.5 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140164239
eCl@ss	27440202 Shell for industrial connectors