

P: +1-727-209-1300 **F**: +1-727-209-1302 coolgear.com



Technical Data Sheet Rev 05.220909

4 Port USB 3.2 Gen 1 Micro Hub PCBA w/ ESD Surge **Protection**

Model Number: CG-MIC4P31H-PCBA









Features

- Has power LED indicating power is on
- Compliant with USB 3.1 specifications
- Supports 15KV ESD surge protection for each port
- Supports +5V DC self-power input
- LED Power indicators

Package Contents

- 2-Pin Terminal Block
- Hub Board Only

nν		

Model No	CG-MIC4P31H-PCBA
Product Type	USB Hub
Compliance	RoHS TAA
UPC	045079163577
Country of Origin	Taiwan
LED indicators	Power
Chipset	GL3522
Electrical Protections	±15kV (air), ±8kV (contact)

PHYSICAL

Ship Weight (lbs)	0.84 lbs
Ship Weight (kg)	0.38 kg
Item Weight	0.063 lbs
Length	3.17 inches
Width	1.58 inches
Height	0.79 inches
Material	N/A
Color	Yellow
Mountable	Bare PCB





Specifications Cont.

Specifications Cont.		
CONNECTIONS		
USB Specification	USB 3.2 Gen 1	
Maximum Data Rate	5 Gbps	
Downstream Port Count	4	
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0	
Works as Standalone Charger	Y - Can be used without Host	
Can be Bus Powered	Y - Supports Bus Power	
Bus Power Isolation Supports Disabling Bus Power	Y	
Power		
Input Voltage	5V DC	
Power Connector	Phoenix 2-pin	
Idle Power Draw	25mA @ 5V Terminal Power	
Max Power Draw	1A(5W)	
Max Per Port Draw	26W	
Supported Charge Protocols	CDP DCP	
ENVIRONMENTAL		
Operating Temperature	0C ~ 55C	
Storage Temperature	-20C ~ 75C	
Operating Humidity	5% to 95% RH	
OS SUPPORT		
Supported Operating Systems	OS independent - No software or drivers required	
WARRANTY		
Warranty Period	1 Year	
PRODUCT URL		
CG-MIC4P31H-PCBA Product Page	https://www.coolgear.com/product/4port-usb-3-1-micro-hub-with-surge-protection-and-mounting-kit	