

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	9/14/20	

SPECIFICATIONS:

Material:
 Housing: PBT, rated UL 94V-0, Color: See Chart
 Cap: See Chart, rated UL 94V-0, Color: See Chart
 Sleeve: Zirconia Ceramic
 Electrical:
 Standards of IEC, EIA/TIA, Telcordia
 Repeatability: 500 min
 Insertion loss: 0.2dB max
 Interchangeability: 0.2dB max
 Repeatability: 0.2dB max
 Temperature Rating:
 Operating temperature: -40°C to +85°C
 Environmental:
 Lead free, RoHS compliant.

OPSB2ANNC1P2	SC/PC ADAPTER LONG EARS (WITH SHRAPNEL) WITH SC CUCURBIT TYPE DUST CAP	PBT 2184C Blue	PP Translucent
OPSA2ANNC1N1	SC/APC ADAPTER LONG EARS (NO SHRAPNEL) WITH SC TWO TYPE DUST CAP	PBT 7737C Green	PBT Black
OPSA2ANNC1P1	SC/APC ADAPTER LONG EARS (WITH SHRAPNEL) WITH SC TWO TYPE DUST CAP	PBT 7737C Green	PBT Black
OPSB2ANNC1N1	SC/PC ADAPTER LONG EARS (NO SHRAPNEL) WITH SC TWO TYPE DUST CAP	PBT 2184C Blue	PBT Black
OPSB2ANNC1P1	SC/PC ADAPTER LONG EARS (WITH SHRAPNEL) WITH SC TWO TYPE DUST CAP	PBT 2184C Blue	PBT Black
PART NUMBER	DESCRIPTION	Housing&Insertcolor	Cap color

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MILLIMETERS TOLERANCES: EXCEPT AS NOTED		909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
MM ANGLE			
X. ± 0.35	X* ± 2°	TITLE SC TYPE ADAPTER, APC&PC, 2 PORTS, LONG EARS, WITH SC TWO TYPE DUST CAP & SC CUCURBIT TYPE DUST CAP	
.X ± 0.30	.X* ± 1°		
.XX ± 0.25	.XX* ± 0.5°		
.XXX ± 0.15	.XXX* ± 0.5°		
APPROVALS		DATE	
DRAWN	OW	9/14/20	
CHECKED	JL	9/14/20	
APPROVED			
SIZE	PART NO.	REV.	
X	OPSX2ANNC1XX	-	
REF:	S00005C	SCALE:	NTS
		SHEET 1 OF 1	

6 5 4 3 2 1