



## Premium 111

### Professional Grade Vinyl Electrical Tape

#### Technical Data Sheet

October 2017

#### Description and Features

**Premium 111** is a 0,18 mm (7 mil) all weather, professional grade, pressure sensitive vinyl tape which applies easily and gives excellent performance over a wide range of temperatures. Cold and weather resistant. Flame retardant. **Premium 111** can be used as primary insulation for splices up to 600 Volts. Use as protective outer jacket over splices and for all low temperature applications.

- Cold and weather resistant
- Flame retardant
- High dielectric strength
- Highly elastic
- Highly conformable
- High UV resistance
- High resistant to sun, water, oil, acids, alkalis, corrosive chemicals
- Meets 2000/53/EC and RoHS 2011/65/EU directives
- Meets ASTM D-3005, Type I; EN 60454-3-1, Type 11; UL 510; CSA C 22.2 no. 197.
- Pb, Cd, Hg, Cr (VI) free

Materials	Backing	Adhesive	Color	Standard Size
	PVC	Rubber based	Black	Width x Length 19 mm x 20 m (0.75 in. x 66 ft.) Other sizes available upon request

Technical Properties	Characteristic	Specification	Typical Value	Test Method
	Thickness, (mm)	0,18±0,025	0,175	ASTM D 1000
	Breaking strength (N/cm)	26 min	30	ASTM D 1000
	Elongation at break (%)	220 min	260	ASTM D 1000
	Adhesion to steel (N/cm)	1,8 min	2,2	ASTM D 1000
	Adhesion to backing (N/cm)	1,8 min	2,2	ASTM D 1000
	Flammability (seconds)	4 max	0	ASTM D 1000
	Flagging (mm)	3 max	0	ASTM D 1000
	Temperature Rating (°C)			
	Maximum	80	80	UL510
		105	105	CSA C 22.2 no.197
	Minimum	-10	-10	UL510
		-18	-18	CSA C 22.2 no 197
	Dielectric Strength (kV)			ASTM D 1000
	-Standard	7 min	8	ASTM D 1000
	-Wet	90%	7,2	ASTM D 1000
	Dielectric Constant	--	3,2	ASTM D 150
	Insulation Resistance (MΩ)	--	1x10 <sup>6</sup>	ASTM D 1000

**Recommended Uses** Used for general splicing purposes. Can be used as primary insulation for splices up to 600 Volts. Provide a protective outer jacket over splices for all low temperature applications. Can be used for wrapping wire harnesses, and insulating degaussing coils.

**Storage** In original packaging, placed in horizontal position under cover and temperature between 5°C and 35 °C, 50-80% R.H.

**Shelf Life** 60 months from date of manufacture.

**LIMITED WARRANTY:** Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (Rev. 01/2017-2019)