

AIMDC-5V Series

The AIMDC-5V Series, by Aim Dynamics, is an optically isolated (3 kV) DC voltage sensing device. It's rated at 1000 Vdc or 100 Vdc, depending on the model, and outputs a proportional 5 Vdc signal.

The AIMDC exceeds 99.5% accuracy at any reading point in its defined voltage range, and is built to withstand harsh temperatures.


The AIMDC is compact and mounts on a DIN rail.

Ruggedized versions of the AIMDC are available, upon request, to withstand greater voltage spikes, electromagnetic interference, electromagnetic pulses, higher humidity, and more.



▲ PRODUCT DIMENSIONS

AIMDC-5V-xxxV I FFT VIFW FRONT VIEW **RIGHT VIEW** -AIMDC-5V-1000V 000 aim BOLATED 56.4 mm 50.4 mm CE SDUCER HIGH VOLTAG 34 mm + V 98 mm 17.5 17.5 mm TOP VIEW



▲ APPLICATIONS

- Solar String Monitoring
- Power Sensing
- Over/Under Voltage Monitoring
- Battery & Energy Storage
- Hydrogen Fuel Cells

▲ AVAILABLE MODELS

- AIMDC-5V-1000V (0-1000 Vdc Input)
- AIMDC-5V-100V (0-100 Vdc Input

SPECIFICATIONS

Primary voltage range	0 – 1000 Vdc; 0 – 100 Vdc
Output	0 – 5 VDC
Accuracy	0.5% over range
Linearity	0.2% over range
Response time	10 ms to 90% voltage range
Working range	5 – 105%
Overload	150% continuous
Temperature	-35° C to +100° C operating -40° C to 100° C storage
L le une telter e	000/
Humidity	90% operating
Isolation	3 kVrms, 1 minute
,	1 5
Isolation	3 kVrms, 1 minute
Isolation Supply voltage	3 kVrms, 1 minute 15 - 36VDC
Isolation Supply voltage Mechanical	3 kVms, 1 minute 15 - 36VDC DIN EN 50 022 or wall mounting
Isolation Supply voltage Mechanical Dimensions	3 kVms, 1 minute 15 - 36VDC DIN EN 50 022 or wall mounting 90 mm W x 56 mm H x 17.7 mm D

▲ FEATURES

- Isolated 1000/100 Vdc Input (depends on model)
- Low Voltage Output
- DIN Rail Mounting
- 0.5% Accuracy
- Screw Type Terminals
- Low Response Time
- Cost-Effective
- Unique Serial Numbers on each unit (option available)
- Batch Test Report (option available)