

6

5

4


3

2

1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/6/07	
A		REDRAWN	8/17/11	



SPECIFICATIONS:
 Material:
 Insulator: PBT, glass reinforced, rated UL 94V-0
 Insulator color: Black
 Contacts: Phosphor Bronze
 Plating:
 Gold flash over Nickel underplate overall

Electrical:
 Current rating: 3 Amp max
 Contact resistance: 30 mohms max
 Insulation resistance: 1,000 Mohms min
 Dielectric withstanding voltage: 650 VAC for 1 minute
Environmental:
 Lead free, RoHS compliant

Positions: 2 thru 10, 13
 A = .100 [2.54] x No. of Positions
 B = .100 [2.54] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	Ø.X ± .10
.XX ± .020	Ø.XXX ± .015
.XXX ± .015	Ø.XXXX ± .010

ADAM TECH
 909 Ratway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .100 [2.54] GANGGED MINI SHUNT, OPEN TOP
 .235 [5.98] HEIGHT, GOLD PLATED

APPROVALS	DATE
DRAWN SS	11/6/07
CHECKED	
APPROVED	

REF: S00078T	SCALE: NTS	SHEET 1 OF 1
SIZE PART NO. X	MSBG-XX-G	REV. A



6

5

4

3

2

1