

## Peak Sensitivity Wavelength: 880nm

The MTD8600N4-T is a photo transistor in a TO-18 metal can dome top package. It is well suited for high reliability and high sensitivity applications.

### FEATURES

- > High Reliability in Demanding Environments
- > Narrow Angular Response
- > Metal Can Package
- > Compact

### APPLICATIONS

- > Optical Switches
- > Edge Sensing
- > Fiber Optical Communications
- > Smoke Detectors



## Absolute Maximum Ratings (Ta=25°C)







| ITEMS                        | SYMBOL | RATINGS    | UNIT |
|------------------------------|--------|------------|------|
| Collector-Emitter Voltage    | Vceo   | 30         | V    |
| Collector-Base Voltage       | Vcbo   | 30         | V    |
| Emitter-Base Voltage         | Vebo   | 5          | V    |
| Emitter-Collector Voltage    | Veco   | 5          | V    |
| Collector Current            | Ic     | 50         | mA   |
| Collector Power Dissipation  | Pc     | 250        | mW   |
| Operating Temperature Range  | Topr   | -30 ~ +100 | °C   |
| Storage Temperature Range    | Tstg   | -40 ~ +125 | °C   |
| Junction Temperature         | Tj     | 125        | °C   |
| Lead Soldering Temperature*1 | Tls    | 260        | °C   |

\*1: Time 5 Sec max, Position: Up to 3mm from the body.

## Electrical & Optical Characteristics (Ta = 25°C)


| ITEMS                       | SYMBOL   | CONDITIONS                           | MIN | TYP      | MAX | UNIT |
|-----------------------------|----------|--------------------------------------|-----|----------|-----|------|
| Collector Emitter Current   | Icel     | Vce=20V, Ee=0.5mW/cm <sup>2</sup> *1 | --  | 3.0      | --  | mA   |
| Collector Dark Current      | Iceo     | Vce=20V, Ee=0mW/cm <sup>2</sup> *1   | --  | --       | 100 | nA   |
| C-E Saturation Voltage      | VCE(sat) | Ic=0.2mA, Ee=5mW/cm <sup>2</sup> *1  | --  | 0.2      | --  | V    |
| Spectral Sensitivity        | λ        | --                                   | --  | 400~1100 | --  | nm   |
| Peak Sensitivity Wavelength | λp       | --                                   | --  | 880      | --  | nm   |
| Switching Time (Rise Time)  | Tr       | RL=100Ω, Vcc=5V, Ic=0.5mA            | --  | 10.0     | --  | μS   |
| Switching Time (Fall Time)  | Tf       | RL=100Ω, Vcc=5V, Ic=0.5mA            | --  | 10.0     | --  | μS   |
| Angular Response            | θ        | --                                   | --  | ±12      | --  | deg  |

\*1: Color Temperature=2870°K Standard Tungsten Lamp.




Unit: mm, Tolerance:  $\pm 0.2$

ANGULAR DISPLACEMENT



THERMAL DERATING CURVE



RELATIVE RESPONSE vs  $\lambda$

