Offset tubular handles

Aluminium







HANDLE SHANKS

Black anodised extruded aluminium, matte finish.

TUBE

Ground aluminium anodised in natural colour.

FITTING ENDS

Glass-fibre reinforced polyamide based (PA) technopolymer, black colour.

STANDARD EXECUTIONS

- RHW1-R: back mounting, threaded blind holes.
- RHW1-F: front mounting, pass-through holes for cylindrical-head screws with hexagon socket, stainless steel nuts and washers, included in the supply.

FEATURES AND APPLICATIONS

RH-W1 series handles are generally used on sliding doors or covers of machines and equipment.

ORDER INFORMATION

The components of RH-W1 handle may also be ordered separately (see table RH-CC) to obtain customised lengths or to add a connecting support, recommended for lengths over 700 mm.

SPECIAL EXECUTIONS ON REQUEST


- Different lengths.
- Anodised aluminium tube, black colour.
- Aluminium handle shanks, anodised in natural colour.


OTHER STANDARD EXECUTIONS AVAILABLE

METRIC

Version RH-W1-CLEAN (see page 587).









RH-CC






















RHW1-R		V								L	METRIC
Code	f	L	d	р	В	h	h1	- 1	l1	12	Δ'Δ
RHW1-30.R200.S01	200	225	M8	15	30	50	33	45	15	25	277
RHW1-30.R300.S01	300	325	M8	15	30	50	33	45	15	25	308
RHW1-30.R500.S01	500	525	M8	15	30	50	33	45	15	25	397

RHW1-F		V								
Code	f	L	d	В	h	h1	1	I 1	12	4,7
RHW1-30.F200.S01	200	225	M6x45	30	50	33	45	15	25	313
RHW1-30.F300.S01	300	325	M6x45	30	50	33	45	15	25	347
RHW1-30.F500.S01	500	525	M6x45	30	50	33	45	15	25	417

