

Infrared ThermometerModel **R2320**





Features

- · Built-in laser pointer identifies target area
- User selectable °F or °C
- 30:1 Distance to Spot size ratio
- Bright color display (EBTN)
- Digitally adjustable emissivity
- Max, Min, Average and Differential readings
- Audible (beep) and visual (tri-color LED) user adjustable alarms
- Internal memory stores up to 5 pre-set high & low alarms and 5 emissivity settings
- Trigger lock and tripod mount for continuous monitoring
- Low battery indication and auto shut off
- · Includes carrying case and battery

Tri-color LEDs quickly indicate when temperatures are within (green), above (red) or below (blue) set parameters.







TECHNICAL DATA

SpecificationsTemperature Range:

Accuracy:

 $3.6^{\circ}F$ (1.8°C) Detailed: \geq 0°C: \pm 1.8°C or \pm 1.8% of reading, whichever

-26 to 1472°F (-32 to 800°C)

Basic: ±1.8% of reading or

is greater

<0°C: \pm (1.8°C+0.1°C/°C) \geq 32°F: \pm 3.6°F or \pm 1.8% of reading, whichever is greater, <32°F: \pm (3.6°F+0.1°F/°F)

0.1°F (0.1°C)

Optical Resolution (D:S): 30:1

Repeatability:

Resolution:

0.7°C or 0.7%, whichever is greater

(1.5°F or 0.7%, whichever is greater)

Spectral Response: 8 to 14µm

Emissivity: 0.1 to 1.0 (Adjustable)

Response Time: 250ms

Backlit Display: Yes (Color EBTN)

Display Hold: Yes

High/Low Alarms: Yes (audible and visual)
Alarm Indicators: LED (High: Red, Low: Blue)

Max/Min: Yes

Average and Differential: Yes
F/C Switchable: Yes
Trigger Lock: Yes
Tripod Mountable: Yes
Laser Class: Class II
Low Battery Indicator: Yes

Power Supply: 9V Battery

Battery Life: Approx. 10 hours (with continuous use,

backlight on)

Product Certifications: CE, RoHS

Operating Temperature: 32 to 122°F (O to 50°C)
Storage Temperature: -4 to 140°F (-20 to 60°C)

Operating Humidity Range: 10 to 90%

Maximum Operating Altitude: 6561' (2000m)

Maximum Storage Altitude: 39370' (12000m)

Dimensions: 7 x 4.98 x 2"

(179 x 126.5 x 53mm)

Weight: 10.95oz (310g)

Model	Description
R2320	Infrared Thermometer
R2320-NIST	Infrared Thermometer with NIST