

# 2SEE



## PERSONAL VISUAL COLLABORATION CAMERA With a four element Beamforming Microphone array



VDO360 introduces their new USB HD Video Camera the 2SEE (SKU VDOS4M), which combines a 1080p camera with far-field voice pick up technology. The 2SEE includes a four microphone array system to provide excellent true voice pick up.

Based on the AI VocalFusion algorithm, the 2SEE series HD Color Video Camera uses Acoustic Echo Cancellation (AEC) and Automatic Noise Suppression(ANS) technologies to get 8 meters of far-field voice pick up, The 2SEE also utilizes the most advanced video processing technology through an Omnivision low-light full HD imaging sensor 1080P HD for image capture.

### Specifications:

#### 2SEE

- 2.1 million pixels, 1/2.7"HD color CMOS
- 4K/15fps 1080@30fps, 720@30fps
- 4 Digital microphones, 8 meter range for voice
- Automatic Echo Cancel (AEC) and Automatic Noise Suppression(ANS) technologies
- Automatic Gain Control (AGC),
- USB2.0 interface plug and play
- 1 year manufacturer's warranty

### Dimensions:

150mmX60mmX30mm (5.9"X2.4"X1.2")- 206g (7.25 oz)

## Technical Parameters

<b>Total Pixels</b>	2 million pixels	<b>Mic array quantity</b>	4
<b>Lens Size</b>	1/2.7 inch	<b>Mic Array Form</b>	linear
<b>Pixel Size</b>	3um	<b>Mic Distance</b>	40mm
<b>Image area</b>	5.85mm×3.27mm	<b>Mic Specification</b>	Digital Mic
<b>Maximum effective pixel</b>	1920 (H) ×1080 (V) 2.1 million pixels	<b>Sampling rate</b>	16KHz/48KHz
<b>Output image format</b>	MJPG and YUY2	<b>Sensitivity</b>	-29dBfs
<b>Resolution</b>	1920*1080@30fps 1280*720@30fps 640*480*30fps	<b>Far-field Distance</b>	0 ~ 8 meters
<b>SNR</b>	39dB	<b>Horizontal Voice Pickup</b>	Horizontal 180°
<b>Dynamic Range</b>	69dB	<b>SNR</b>	65.5dB
<b>Sensitivity</b>	0.65V/lux-sec@550nm	<b>Communication Mode</b>	full duplex
<b>Minimum illumination</b>	0.5lux	<b>AEC</b>	Up to 50dB
<b>Interface type</b>	USB 2.0 High Speed	<b>Noise suppression</b>	Up to 15dB
<b>Driver</b>	USB Video Class(UVC)		
<b>AIC</b>	Automatic Exposure (AE) Auto White Balance (AWB) Automatic Gain Control (AGC) Dynamic Black Level Calibration (ABLC)		
<b>OS Support</b>	WinXP/Vista/Win7/Win8/Win10 Linux with UVC (above linux-2.6.26) MAC-OS X 10.4.8 or later WinCE with UVC Android 4.0 or above with UVC		
<b>Field of view</b>	75°(W)		
<b>Power</b>	USB 5V		

