

## Han PP Power L metal housing



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 004 0301
Specification	Han PP Power L metal housing
HARTING eCatalogue	<a href="https://b2b.harting.com/09350040301">https://b2b.harting.com/09350040301</a>

### Identification

Category	Connectors
Series	Han® PushPull (V14)
Type of hood/housing	Bulkhead mounted housing

### Version

Locking type	PushPull
--------------	----------

### Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances	Not contained
-----------------------	---------------

## Specifications and approvals

Specifications	IEC/PAS 61076-3-126
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size	1
Net weight	24.52 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140053847
eCl@ss	27440202 Shell for industrial connectors