

Carrier_BT494030_SOT23-6_h

Part number	78 01 030 0003
Specification	Carrier_BT494030_SOT23-6_h
HARTING eCatalogue	https://b2b.harting.com/78010300003

Identification

Category	Surface Mount Device
Series	3D-MID
Element	Carrier for electronic components
Specification	Interconnection
Features	Other materials or trace layouts on request!
Version	
Fixing	PCB assembly (SMD)
Pack contents	Tape & reel 3400 pieces on reel Lower quantities available on request!

Technical characteristics

Operating temperature	-40 +125 °C
Storage temperature	-40 +125 °C

Material properties

Material	Liquid crystal polymer (LCP)
Surface (contacts)	Au (≥0.05 μm) over Ni (≥4 μm) over Cu (511 μm)
Length	4.9 mm
Width	4 mm
Height	3 mm
Commercial data	
Packaging size	1,700

Page 1 / 6 | Creation date 2023-01-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Commercial data

Country of origin	Switzerland
European customs tariff number	85340019
GTIN	5713140277403
eCl@ss	27469090 PCB connection technology (other, unspecified)


Other materials or trace layouts on request!





Page 2 / 6 | Creation date 2023-01-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany




Drawing (dimensions in mm)











Page 3 / 6 | Creation date 2023-01-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

PICK & PLACE AREA







Drawing (dimensions in mm)











CARRIER PATTERN LAYOUT




RECOMMENDED PCB PATTERN LAYOUT



Soldering instructions




PB-free soldering profile (J-STD-020C)



Page 5 / 6 | Creation date 2023-01-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Tape layout & packaging



Page 6 / 6 | Creation date 2023-01-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany