

TECHNICAL DATA



Features

- True RMS measures frequency, resistance, capacitance and temperature
- Diode check and continuity functions
- Backlit LCD readout with analog bar graph
- 4-20 mA process loop measurements with % readout
- Data hold, Max/Min and Peak capture mode
- IP67 dust and waterproof
- Cat. IV 600V, Cat. III 1000V safety rating
- Includes Thermocouple Adapter, thermocouple wire probe (Type K), test leads, battery, weatherproof plugs, and carrying case

Specifications

AC/DC Voltage

Range: AC: 400mV, 4, 40, 400, 1000V
DC: 400mV, 4, 40, 400, 1000V

Accuracy: AC: 400mV $\pm(1.0\% \text{ rdg.} + 5 \text{ dgt.})$
4, 40, 400, 1000V $\pm(1.0\% \text{ rdg.} + 3 \text{ dgt.})$
DC: 400mV/4,40,
400V $\pm(0.06\% \text{ rdg.} + 2 \text{ dgt.})$
1000V $\pm(0.1\% \text{ rdg.} + 5 \text{ dgt.})$

Resolution: AC: 0.1mV, 0.001, 0.01, 1V
DC: 0.01mV, 0.0001, 0.01, 0.1V

AC/DC Current

Range: 400, 4000 μ A, 40, 400mA, 10A

Accuracy: AC: $\pm(1.5\% \text{ rdg.} + 3 \text{ dgt.})$
DC: $\pm(1.0\% \text{ rdg.} + 3 \text{ dgt.})$

Resolution: AC: 0.1, 1 μ A, 0.01, 0.1mA, 0.01A
DC: 0.01, 0.1 μ A, 0.001, 0.01mA, 0.001A

Resistance

Range: 400 Ω , 4, 40, 400k Ω , 4, 40M Ω

Accuracy: 400 Ω : $\pm(0.3\% \text{ rdg.} + 9 \text{ dgt.})$
4, 40, 400k Ω , 4M Ω : $\pm(0.3\% \text{ rdg.} + 4 \text{ dgt.})$
40M Ω : $\pm(2.0\% \text{ rdg.} + 10 \text{ dgt.})$

Resolution: 0.01 Ω , 0.0001, 0.001,
0.01k Ω , 0.001M Ω

Capacitance

Range: 40, 400nF, 4, 40, 400, 4000 μ F, 40mF

Accuracy: 40, 400nF: $\pm(3.5\% \text{ rdg.} + 40 \text{ dgt.})$
4, 40, 400 μ F: $\pm(3.5\% \text{ rdg.} + 10 \text{ dgt.})$
4000 μ F, 40mF: $\pm(5\% \text{ rdg.} + 10 \text{ dgt.})$

Resolution: 0.001, 0.01nF, 0.0001, 0.001,
0.01, 0.1 μ F, 0.001mF

Frequency

Range: 40, 400Hz, 4, 40, 400kHz, 4, 40, 100MHz

Accuracy: $\pm(0.1\% \text{ rdg.} + 1 \text{ dgt.})$

Resolution: 0.00, 0.01Hz, 0.0001, 0.001,
0.01kHz, 0.0001, 0.001, 0.01MHz

Temperature

Range: -58 to 1832 $^{\circ}$ F (-50 to 1000 $^{\circ}$ C)

Accuracy: $\pm(1.0\% \text{ rdg.} + 4.5^{\circ}$ F)
 $\pm(1.0\% \text{ rdg.} + 2.5^{\circ}$ C)

Resolution: 1 $^{\circ}$ F, 1 $^{\circ}$ C

4-20mA%

Range: -25 to 125%

Accuracy: $\pm(50 \text{ dgt.})$

Resolution: 0.01%

Continued...

TECHNICAL DATA



General Specifications

| | |
|--------------------------|---|
| Range Selection: | Autoranging/Manual |
| True RMS: | Yes |
| Display: | 40,000 count LCD display |
| Display Hold: | Yes |
| Max/Min: | Yes |
| Peak Hold: | Yes |
| Relative Mode: | Yes |
| Diode Test: | Yes |
| Backlit Display: | Yes |
| Digital Analog Bargraph: | Yes |
| Continuity Check: | Audible signal if resistance $\leq 35\Omega$ |
| Duty Cycle: | Yes (0.1 - 99.9%) |
| Kick Stand: | Yes |
| Auto Power Off: | Yes (after 15 minutes) |
| Power Supply: | 9V Battery |
| Low Battery Indicator: | Yes |
| Fuse Protection: | Yes |
| Replaceable Test Leads: | Yes |
| Overvoltage Category: | CAT. IV 600V, CAT. III 1000V |
| Product Certifications: | CE, IP67, Drop Tested (2M) |
| Operating Temperature: | 41 to 104°F (5 to 40°C) |

| | |
|----------------------|---------------------------------------|
| Storage Temperature: | -4 to 140°F (-20 to 60°C) |
| Dimensions: | 7.4 x 3.2 x 2.0" (187 x 81 x 50mm) |
| Weight: | 12oz (342g) |

| Model | Description |
|---------------|--|
| R5010 | True RMS Digital Multimeter |
| R1020 | Fused Test Lead Set |
| CP-09 | AC Current Adapter |
| R2990 | Thermocouple Adapter |
| R2920 | Surface Thermocouple Probe |
| R2930 | Right Angle Thermocouple Surface Probe |
| R2950 | Immersion Thermocouple Probe |
| TP-01 | Type K Thermocouple Wire Probe |
| R1000 | Safety Test Lead Set, Double Insulated |
| F-500mA/1000V | Replacement Fuse |
| F-10A/1000V | Replacement Fuse |
| CA-05A | Soft Carrying Case |
| R5010-NIST | True RMS Digital Multimeter & NIST |